CERTIFICATE

Certificate number: 2207729 (1)

Issued *26/07/2022*
Expires *26/07/2027*

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)
Model number(s) – see Appendix

Ariston S.p.A.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.
Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.
See https://www.kiwa.com/gb/en/about-kiwa/water-products/ to ensure that the certificate is still valid.

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Ariston SpA
Viale Aristide Merloni 45
60044 Fabriano (AN)
ITALY

Product Certificate

Appendix to Certificate number: 2207729

The following products belong to this certificate

PRODUCT DESCRIPTION Range of cased and insulated directly heated unvented water heaters with enamel coated steel cylinders. Models supplied with a pressure relief valve set at 6 bar and tundish arrangement. ATS3 – Without Production Surveillance.
MODEL(S) 3100831 – Andris R 10 OR 3kW EU; 3100832 – Andris R 10 UR 3kW EU; 3100833 – Andris R 15 OR 3kW EU; 3100834 – Andris R 15 UR 3kW EU; 3100863 – Andris R 10 UR 2kW EU; 3100834 – Andris R 15 UR 2kW EU; 3100865 – Andris R 10 UR 2kW PL EU; 3100866 – Andris R 15 UR 2kW PL EU.
SIZE: ½" BSP(M).
SCOPE: Manufacturer recommended maximum working pressure 5.5 Bar & maximum operating temperature 74°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 74°C.
MARKING Ariston, model, serial no, pressure rating and other technical information on body.
MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.
BACKFLOW PROTECTION NOTES Consideration must be made on installation to the airgap arrangement.
ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.

Extra Notes